



[WWW.TNTRESCUE.COM](http://WWW.TNTRESCUE.COM)



# INDEX

WELCOME	PG 1
FOREVER WARRANTY	PG 2
CUTTERS	PG 4-5
COMBINATION CUTTER / SPREADER	PG 6
SPREADERS	PG 7-9
RAMS	PG 10-11
ACCESSORIES	PG 12-13
ISO	PG 14
CONTACT	PG 15





Welcome to TNT Rescue Systems, Inc, the premier manufacturer of Powered Hydraulic Rescue Tools. The employees and distributors are delighted with your interest in our products and look forward to a long and mutually beneficial relationship.

Blanton & Company began as an OEM manufacturer of Industrial hydraulic pumps. Entry into the rescue tool world came by way of one of our early customers, with the Blanton design of the first true 2 tool simultaneous operation pump. Owner and President Tom Blanton, noted a lack of customer service in the rescue tool market, creating the initial vision of what would become TNT Rescue Systems, Inc.

TNT Rescue Systems Inc's vision is simple: design, build, and distribute the highest quality hydraulic rescue tools, provide a Forever Warranty and support the customer with the highest level of service.

The dedication to service is shown everyday by the family of TNT Rescue Systems, Inc. From employees at the factory, management, or our dealers we have current and retired firefighters throughout our organization and fully understand the expectations of tool performance on the street.

TNT Rescue Systems, Inc. understands the service you need from you rescue tools and your tool manufacturer. Dedication to our customers continues with our Forever Warranty. Our warranty is the most comprehensive in the industry, providing coverage for our products. Whether you're a dealer or end user we are committed to providing you with exceptional customer service. Our customer-focused method of doing business has been the standard at TNT Rescue Systems Inc, ( Blanton & Company ) since its start in 1986.

TNT Rescue Systems, Inc. is 100% owned and operated with our only facility solely located in Ashippun, Wisconsin.

To that end, TNT Rescue Systems, Inc. is a ISO 9001:2015 registered company and builds tools to exceed the minimum performance standard of NFPA 1936 & EN 13204





CONTACT YOUR LOCAL DEALER FOR MORE INFORMATION ON THE TNT FOREVER WARRANTY OR  
ALTERNATIVELY VISIT OUR WEBSITE:  
[WWW.TNTRESCUE.COM](http://WWW.TNTRESCUE.COM)





**THE ULTIMATE COMBINATION FOR SPEED,  
POWER AND QUALITY!**

# **STORM SURGE**

**TNT RESCUE SYSTEMS STORM-SURGE  
SERIES BATTERY OPERATED EXTRICATION  
TOOLS ARE POWERED BY THE  
MILWAUKEE M18 PLATFORM , PAIRING THIS  
WITH THE MILWAUKEE M18 8AH BATTERY  
MAKES IT THE LONGEST RUNNING  
PORTABLE RESCUE TOOL IN THE MARKET.**

**POWERED BY  
M18 REDLITHIUM**





**ESLC-29-18V**



**STORM SURGE**

**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	32.99 IN	837.90 MM
HEIGHT	11.69 IN	296.83 MM
WIDTH	10.5 IN	266.7 MM
WEIGHT		
EXCL. BATTERY	51.10 LBS	23.18 KG
INCL. BATTERY	53.50 LBS	24.26 KG
MAX. BLADE OPENING	8 IN	203 MM
MAX. CUT REACH	5.08 IN	129.15 MM
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B9, C9, D9, E9, F4	
IP RATING	54	

**4**





**EBFC-320-18V**



**STORM SURGE**

**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	35.81 IN	909.69 MM
HEIGHT	11.81 IN	299.91 MM
WIDTH	10.50 IN	266.70 MM
WEIGHT		
EXCL. BATTERY	61.20 LBS	27.76 KG
INCL. BATTERY	63.55 LBS	28.84 KG
MAX. BLADE OPENING	10.12 IN	257.06 MM
MAX. CUT REACH	5.55 IN	140.96 MM
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
NFPA CUT TEST	A9, B9, C9, D9, E9, F5	
IP RATING	54	





**EBFCC-28-18V**



**STORM SURGE**

**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	36.21 IN	919.79 MM
HEIGHT	11.74 IN	298.13 MM
WIDTH	10.5 IN	266.7 MM
WEIGHT		
EXCL. BATTERY	53.00 LBS	24.04 KG
INCL. BATTERY	55.04 LBS	25.12 KG
MAX. BLADE OPENING	13.5 IN	342.9 MM
MAX. CUT REACH	3.95 IN	100.39 MM
MAX. SPREAD DISTANCE	16.64 IN	422.66 MM
MAX. SPREAD FORCE	286,000 LBS	1,272 KN
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
NFPA CUT TEST	A8, B9, C8, D8, E9, F4	
IP RATING	54	







**ES100-24-18V**



**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	32.43 IN	823.77 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	46.80 LBS	21.22 KG
INCL. BATTERY	49.20 LBS	22.30 KG
MAX. SPREAD DISTANCE	24 IN	609.6 MM
MAX. PULL DISTANCE	20.22 IN	513.56 MM
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
MAX. SPREAD FORCE RANGE	64,476 - 242,368 LBS	286 - 1,078 KN
MAX. PULL FORCE	29,307 LBS	130 KN
IP RATING	54	





# ES100-28-18V



**POWERED BY**  
**M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	34.80 IN	883.99 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	48.20 LBS	21.88 KG
INCL. BATTERY	50.60 LBS	22.99 KG
MAX. SPREAD DISTANCE	28 IN	711.2 MM
MAX. PULL DISTANCE	24.26 IN	616.31 MM
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
MAX. SPREAD FORCE RANGE	56,128 - 228,126 LBS	249 - 1,014 KN
MAX. PULL FORCE	25,512 LBS	113 KN
IP RATING	54	





# ES100-32-18V



## STORM SURGE

**POWERED BY**  
M18 REDLITHIUM

TECHNICAL SPECS	STANDARD	METRIC
LENGTH	37.17 IN	944.16 MM
HEIGHT	11.15 IN	283.09 MM
WIDTH	13.58 IN	344.93 MM
WEIGHT		
EXCL. BATTERY	49.40 LBS	22.40 KG
INCL. BATTERY	51.75 LBS	23.48 KG
MAX. SPREAD DISTANCE	32 IN	812.8 MM
MAX. PULL DISTANCE	28.3 IN	718.93 MM
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
MAX. SPREAD FORCE RANGE	50,592 - 201,420 LBS	225 - 895 KN
MAX. PULL FORCE	23,041 LBS	102 KN
IP RATING	54	





**ER-40-18V**



**STORM SURGE**

**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
EXTENDED LENGTH	41 IN	1041.4 MM
CLOSED LENGTH	25.50 IN	647.7 MM
HEIGHT	10.75 IN	273 MM
WIDTH	8.10 IN	205.7 MM
WEIGHT		
EXCL. BATTERY	41.20 LBS	18.70 KG
INCL. BATTERY	43.60 LBS	19.78 KG
MAX. PUSH FORCE	32,980 LBS	145 KN
MAX. PULL FORCE	7,800 LBS	34.7 KN
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
STROKE	13.97 IN	355 MM
IP RATING	54	

**10**





**ETLS-40-18V**



**STORM SURGE**

**POWERED BY  
M18 REDLITHIUM**

TECHNICAL SPECS	STANDARD	METRIC
EXTENDED LENGTH	42.25 IN	1073.15 MM
CLOSED LENGTH	21.50 IN	546.1 MM
HEIGHT	10.75 IN	273 MM
WIDTH	8.10 IN	205.7 MM
WEIGHT		
EXCL. BATTERY	39.05 LBS	17.72 KG
INCL. BATTERY	41.45 LBS	18.80 KG
1ST STAGE PUSH FORCE	32,597 LBS	145 KN
2ND STAGE PUSH FORCE	12,881 LBS	57.3 KN
POWER SOURCE	MILWAUKEE M18	
MFG. TO NFPA 1936-2020	YES	
1ST STAGE STROKE	12.95 IN	329 MM
2ND STAGE STROKE	8.70 IN	221 MM
IP RATING	54	



**11**



# ACCESSORIES

## RAM BASE EXTENSION KIT



TECHNICAL SPECS	STANDARD	METRIC
<b>6 INCH RAM BASE EXTENSION</b>		
EXTENSION BASE	1.35 IN	34.13 MM
EXTENSION HEAD	3 IN	76.20 MM
ASSEMBLED LENGTH	10.35 IN	262.73 MM
<b>12 INCH RAM BASE EXTENSION</b>		
EXTENSION BASE	1.35 IN	34.13 MM
EXTENSION HEAD	3 IN	76.20 MM
ASSEMBLED LENGTH	16.35 IN	415.29 MM
<b>18 INCH RAM BASE EXTENSION</b>		
EXTENSION BASE	1.35 IN	34.13 MM
EXTENSION HEAD	3 IN	76.20 MM
ASSEMBLED LENGTH	22.35 IN	567.69 MM

**12**





# ACCESSORIES

**R-KIT FITS ER-40-18V**

**570220 M18 8AH**



**XR-KIT FITS ER-40-18V**

**570221**





FOR MORE DETAILED SPECIFICATIONS  
PLEASE VISIT OUR WEBSITE:

**[WWW.TNTRESCUE.COM](http://WWW.TNTRESCUE.COM)**

TNT RESCUE SYSTEMS INC.  
2490 WEST OAK STREET  
ASHIPPUN, WI 53003 USA  
email: [contactus@tntrescue.com](mailto:contactus@tntrescue.com)



**14**







## **ISO 9001:2015**

The International for Standardization (ISO) is a network of national standards instituted in 157 countries. Each ISO member is the leading standards organization in its country. These members devise new standards, work to advance them, and team up with the ISO Central Secretariat to guide the technical groups that develop them.

They award certification only after registered, independent auditors review a company's process against strict ISO standards, and verify that the company has met established requirements, in both policy and practice.

TNT Rescue Systems Inc. is certified as an ISO 9001:2015 registered firm. This means you can be sure that TNT Rescue Systems Inc. products are designed and manufactured to the high standards our industry - and the ISO - demands. Certification covers all that we do to enhance customer satisfaction by meeting both customer and regulatory requirements, while continually improving performance.

**PERFORMANCE.  
QUALITY  
SERVICE  
GUARANTEED!**



**15**

**BUILT TO  
RESCUE**

